
# BRIGHTWELL



# SUCTION LANCE



#### Description

Industrial suction lances designed for dispensing liquid detergents and additives in automatic dosing systems

- Available in various options, compatible with a wide range of containers (jerrican, canisters, drums, IBCs...) and sizes (20 L, 100 L, 200 L, 1000 L)
- Capable of feed up to three dosing systems from a single container, reducing the need of multiple containers.
- Precision & Safety: the float switch assembly ensures accurate chemical level monitoring and triggers an alarm when levels are low, preventing inconsistent dosing
- Made in polypropylene to guarantee chemical compatibility with detergents and additives
- Equipped with a foot valve system that prevents chemical spillage during changing drums and keeps pipelines primed, ensuring proper flow
- Includes a filter to prevent solid particles or clumps from entering the pipelines
- High suction capacity: they can handle high flow rates, ensuring efficient dosing in high-demand industrial installations.

		Value	
MATERIALS	Body	PP polypropylene	
CONNECTORS	Outlet barb diameter	10mm barbed	
	Outlet barb material	PVDF	
	Fittings (straight / elbows)	PP for pipe 10/12	
	Recommended pipes for installation	Braided (UK & US) PVC 10x16	
ELECTRICAL PARAMETERS	Voltage	24 V DC	
VARIATIONS	<b>Containers:</b> - 20 Litres - 100 Litres - 200 Litres - 1000 Litres	Suction Outlets: - 1 suction outlets - 2 suction outlets - 3 suction outlets	


### **Technical Specifications**

T +44 (0) 1273 513566 E sales@brightwell.co.uk W brightwell.co.uk Unit 9, Euro Business Park, Estate Road, Newhaven, East Sussex BN9 ODO All information in this data sheet is correct at the time of printing and is subject to change without notice.

#### **PP Suction Lance with Integrated Float Switch**


Part Code	Container Size	Suction Outlets	Length	Diameter
A500SL1SP20LPP	20 L CONTAINER	1	570 mm	46 mm
A500SL2SP20LPP	20 L CONTAINER	2	570 mm	46 mm
A500SL3SP20LPP	20 L CONTAINER	3	570 mm	46 mm
A500SL1SP100LPP	100 L CONTAINER	1	925 mm	58 mm
A500SL2SP100LPP	100 L CONTAINER	2	925 mm	58 mm
A500SL3SP100LPP	100 L CONTAINER	3	925 mm	58 mm
A500SL1SP200LPP	200 L CONTAINER	1	1110 mm	58 mm
A500SL2SP200LPP	200 L CONTAINER	2	1110 mm	58 mm
A500SL3SP200LPP	200 L CONTAINER	3	1110 mm	58 mm
A500SL1SP1000LPP	1000 L CONTAINER	1	1320 mm	58 mm
A500SL2SP1000LPP	1000 L CONTAINER	2	1320 mm	58 mm
A500SL3SP1000LPP	1000 L CONTAINER	3	1320 mm	58 mm

#### Diagram



## Connections

- 1 24 VDC input to Multiplex unit
- 2 Chemical out to Multiplex inlet



T +44 (0) 1273 513566 E sales@brightwell.co.uk W brightwell.co.uk Unit 9, Euro Business Park, Estate Road, Newhaven, East Sussex BN9 0DQ

All information in this data sheet is correct at the time of printing and is subject to change without notice.